### Computational Analysis of TAPIRO Experiments by the SERPENT and ERANOS Codes

O. Dicuonzo\*, V. Fabrizio<sup>†</sup>, D. Caron\*, S. Dulla\*, M. Carta<sup>†</sup>, P. Ravetto\*

\*Politecnico di Torino, Dipartimento Energia, Corso Duca degli Abruzzi, 24 - 10129 Torino, Italy <sup>†</sup>ENEA, Centro Ricerche Casaccia, Via Anguillarese, 301 - 00123 S. Maria di Galeria (Roma), Italy ortensia.dicuonzo@studenti.polito.it, valentina.fabrizio@enea.it, dominic.caron@polito.it, sandra.dulla@polito.it, mario.carta@enea.it, piero.ravetto@polito.it

**Abstract** - The TAPIRO experimental reactor is modelled by the Monte Carlo code SERPENT and the deterministic code ERANOS. The results of the simulations of some measurements performed on the reactor in the past are compared to the experimental data. The analysis of the results is focused on the role of cross section data libraries, on the approximation in the modelling associated to the use of deterministic tools and on the need of nuclear data, with special regards to copper, being a relevant component in the TAPIRO reactor.

## I. INTRODUCTION

In the evaluation of the approaches to the simulation of nuclear fission systems, integral measurements are of fundamental importance, as they allow to assess the various constituents of the approach adopted in the analysis: physical models, numerical methods and nuclear data. At present, a work is in progress to assess a set of integral measurements resulting from an experimental campaign performed on the TAPIRO research reactor [1] some years ago. The final objective of the activity is to employ the data acquired through the experiments in a nuclear data adjustment procedure [2]; this objective is foreseen to be achieved in two phases. First, the TAPIRO reactor is to be simulated by the Monte Carlo method and by a deterministic approach. The neutronic simulation allows to calculate the reaction rates and therefore, by direct comparison with the measured values, to verify the suitability of the TAPIRO modelling approach, regarding both the codes and the data libraries. Second, an investigation on the effect of the cross section data used in the prediction of the quantities measured in the experiments is to be performed, as the sensitivity of integral parameters to cross section data is essential to the adjustment formalism.

The present work describes the first part of the activity and focuses on the simulation of the TAPIRO reactor and the experimental campaign using the Monte Carlo and deterministic methods. First, the basic features of the TAPIRO reactor and the nature and scopes of the experimental campaign are summarised. Next, the modelling approach is described, both in relation to the model of the reactor and as regards the representation of the experiment. Finally, some computational results of the model are compared and discussed, using different cross section data libraries. Due to the relevant contribution of copper to the neutronics of this system, the effects of its properties are also preliminarily analysed.

# II. THE TAPIRO REACTOR AND THE EXPERIMEN-TAL CAMPAIGN

The TAPIRO (**TA**ratura **PI**la **R**apida Potenza Zer**O**) reactor (Fig. 1) is a fast spectrum research reactor of the Italian National Agency for New Technologies, Energy and Sustainable Economic Development (ENEA) laboratories, located

in Casaccia, Italy [1]. The core of the TAPIRO reactor is a square cylinder (diameter about 12 cm). The fuel is made of a highly-enriched uranium-molybdenum alloy (98.5 wt.% U–1.5 wt.% Mo). The maximum operating power is 5 kW, producing a flux of about  $4 \cdot 10^{12}$  n/(cm<sup>2</sup>s) at the core centre. Additional design characteristics are summarised in Table I.



Fig. 1. Irradiation facilities of TAPIRO [1]: 1) diametral channel; 2) tangential channel; 3) radial channel 1; 4) radial channel 2; 5) detector channels; 6) paraffin; 7) thermal column.

The irradiation channels (Fig. 2) allow to insert devices also in high flux regions. They are enclosed in a metallic jacket and have a reducing section going toward the core to limit the gamma streaming effect. Each channel plug is constituted by a casing filled with shielding material and it is provided with a copper extension placed in the reflector zone. This extension may be modified to host the sample container [1].

All the control rods are made of copper: the shim rods are used to control the nominal power, the regulation rod movement ensures the fine adjustment of the criticality and the safety rods allow the scram. During normal operation, all control rods are inserted. When extracted, they are hosted in a sort of plenum of air in the inner reflector and the remaining void is replaced by about 15 cm of air [3]. The thermal column provides an epithermal flux [1]. TABLE I. Characteristics of the TAPIRO reactor [1].

CORE

- Cylindrical: diameter about 12 cm
- Diameter/height: about 1
- FUEL
- Uranium-molybdenum alloy (98.5 wt.% U-1.5 wt.% Mo)
- Density: 18.5 g cm<sup>-3</sup>
- Enrichment: 93.5% <sup>235</sup>U

REFLECTOR

- Cylindrical Inner Reflector: diameter 34.8 cm
- Outer Reflector: diameter 80 cm
- Overall Height: 70 cm
- Material: Copper
- COOLING SYSTEM
- Forced He: 100 g/s @ 7.5 ata
- **BIOLOGICAL SHIELD**
- Shape: near spherical
- Thickness: 175 cm
- Material: high density borate concrete
- IRRADIATION CHANNELS
- 3 channels at the reactor mid-plane
- 1 tangential (to the top edge of the core)
- CONTROL RODS
- 2 Shim Rods + 2 Safety Rods + 1 Regulation Rod



Fig. 2. Section of the reactor parallel to the floor of the reactor room at 100 cm height [1]: 1) source channel; 2) tangential channel; 3) diametral channel; 4) horizontal channel thermal column 1; 5) horizontal channel thermal column 2; 6) thermal column; 7) safety rod 1; 8) regulation rod; 9) shim rod 1; 10) shim rod 2; 11) safety rod 2; 12) radial channel 1; 13) grand horizontal channel; 14) radial channel 2.

In the framework of a collaborative agreement between ENEA and the Studiecentrum voor Kernenergie / Centre d'Etude de l'Energie Nucléaire (SCK•CEN) of Belgium, an experimental campaign was carried out on the TAPIRO reactor from 1980 to 1986 [4]. The objective of the irradiation campaign was to provide a neutronic characterisation of the TAPIRO reactor, which revealed several interesting features of the neutron flux distribution (both spatial and energetic) of the reactor, among which includes a spherical symmetry of the flux with respect to the core centre.

As part of the experimental campaign, the reaction rates of different isotopes were measured in all irradiation channels existing in TAPIRO. In this work, we focus on the fission rates of Np-237, U-238 and U-235 measured along the radial channel 1 by miniature fission chambers (diameter 1.5 mm, length 0.4 mm [4]). The count rates recorded by these devices are compared with the computed results, taking into account the uncertainties of both experimental and computed results.

#### **III. THE TAPIRO MODELS**

In this section, the two models utilised to describe the system are presented, together with the approximations introduced to implement them into the computational codes.

#### 1. The SERPENT Monte Carlo model

A previously developed model of the TAPIRO reactor [3] that was implemented in the SERPENT Monte Carlo code (version 1.1.19) [5] has been modified in order to describe the configuration of the reactor during the experimental campaign.

The geometry of TAPIRO implemented in the SERPENT model includes: the core, the primary circuit for the core cooling, the inner and outer reflectors (Fig. 3) and the diametral channel, the tangential channel and the radial channel 1. The core centre corresponds to the centre of the frame of reference used in the model. The radial channel 1 is parallel to the x-axis, instead the tangential and diametral channel to the y-axis.

The radial channel 2 and the source channel are not considered, since the work presented does not involve a neutronic characterisation of those regions. Instead, within the reflector, these regions are assumed to contain the reflector material, which is the same as that of the plug in the same region. Outside of the reflector, these channels are considered to be part of the biological shield in the model. These approximations are necessary due to limitations of geometry capabilities of the version of the code in use, but are not foreseen to introduce a large error in the representation of the reactor for the experiments, as these regions are neutronically far from the channels in which the measurements are carried out and the channels not involved in the measurements are filled with the plug. The material compositions have been provided by ENEA.

The concrete shield that surrounds the thermal column is simplified in the model with respect to the reality: it consists of a regular parallelepiped. This approximation is acceptable since the region has a negligible neutronic relevance with regard to the experiments [3].

In Table II, the positions of the control rods during the experiment are reported. Control rod positions are measured



Fig. 3. A xy-section extended to the outer reflector radius at z=1 cm at the same orientation as in Fig. 2 (IR: inner reflector, OR: outer reflector).

relative to the top of the core. The control rod level equal to 15 cm for the shim and regulation rods corresponds to the full insertion of the rod at the height of the top of the core ( $z \approx 5.55$  cm in the reference frame of the model). The safety rods are inserted at  $z \approx 4$  cm in the reference frame of the model.

TABLE II. Control rods level in the reference frame of the control rods [4].

position [cm]
10.0 9.25 13.4

In Fig. 3, an axial section of the model is shown at the position z=1 cm. At that height, the shim rods and the regulation rod are extracted (Table II), so the channels contain air. The other rods are inserted at that height.

The radial channel 1 (Fig. 4) penetrates in the inner reflector and reaches the limit of the biological shielding (220 cm from the core centre). To obtain the fission rates traverse of this channel, a square access groove (0.5 mm side) was bored in the centre of the plug for the whole length of the radial channel 1 [4]. In the model (Fig. 5 a)), the form of the access groove is cylindrical. The fission chamber is placed on a copper insert (Fig. 5 b)) that covers the half of the access groove length, the fission chamber can record the fission rate in selected points of measurement.

Since the measurement points are different for different isotopes, a simplified approach is adopted (avoiding different Monte Carlo simulations for each point of measurement for all nuclides): the copper insert is placed in a certain position



Fig. 4. A xy-section of the radial channel 1 at z=0: a) the channel is entirely closed by plug; b) the copper insert is partially extracted in the reflector zone (the detectors are placed in the preceding access groove region); c) the copper insert is extracted to the farthest point of measurement (the detectors are placed in the preceding access groove region starting from plane P). The plane P is at the same position in which the copper insert is placed in b). The materials to which the colours correspond are the same as those labelled in Fig. 3.



Fig. 5. a) A yz-section of the radial channel 1 at x=18 cm (the position of the plane A in the Fig. 4 b)), in which the model of the access groove and the real one are compared. b) A yz-section of the radial channel 1 at x=36 cm (the position of the plane B in the Fig. 4 b)), in which the model of the copper insert is shown.

in the radial channel 1, and the detectors are positioned in the preceding void part of the access groove.

The copper insert is moved in two positions: one in the reflector zone and one in the shielding zone. The point in which the copper insert is placed in the reflector zone is decided by examining the results of an exploratory simulation in which the copper insert is placed in the furthest point of measurement among all the nuclides (about 61.5 cm, in the shielding zone, see Fig. 4 c)). A second simulation is performed moving the copper insert in the place in which the experimental and simulated fission rates start to diverge (about 26.45 cm). Thanks to the displacement of the copper insert, the experimental and simulated results in the first part of the traverse show a better agreement than in the exploratory simulation [6].

Indeed, the spectrum in the two parts of the traverse (the simulations set-up in Fig. 4 b) and Fig. 4 c)) is different, so to approximate the whole traverse with a single simulation introduces a greater error with respect to the approach of splitting the traverse. In Fig. 6, the spectral indexes in the different regions of radial channel 1 (Fig. 7) are shown. For the purpose of this analysis, the spectral index is defined as

$$I_{kf}(E_g) = \frac{1}{\Psi_{kf}} \int_{\vec{r} \in V_k} d\vec{r} \int_{E_g}^{E_{g-1}} dE \, \Phi(\vec{r}, E), \tag{1}$$

which is the scalar flux  $\Phi$  integrated in space in the region k and in the energy range  $[E_g; E_{g-1}]$ , divided by

$$\Psi_{kf} = \int_{\vec{r} \in V_k} d\vec{r} \int_{E_f}^{E_{f-1}} dE \, \Phi(\vec{r}, E), \tag{2}$$

which represents the flux integrated in space in the same region k and in a reference energy range  $[E_f; E_{f-1}]$ . A logical choice of the reference energy range for a system in which the core material is highly-enriched U-235 is around the most probable energy at which a neutron is born from fission of that isotope. The energy discretisation adopted for analysis of the spectral indexes in the SERPENT model is consistent with that used by the ERANOS model of TAPIRO.



Fig. 6. Comparison of the spectral indexes in the different regions between the first and the second part of the traverse.



Fig. 7. Radial discretisation of radial channel 1 in zones on which the flux is integrated.

The simulation mode is the criticality source method: the inactive cycles are 30, the active ones are 2000 to simulate

the fission rates distribution in the first part of the traverse, 3500 for the second part: more cycles are necessary since the statistics gets poorer moving away from the core. The number of source neutrons per cycle has been set equal to  $2 \cdot 10^7$ . The calculations are performed for the reference simulations employing the JEFF-3.1.1 cross section library [7]; all cross sections are evaluated at 293 K.

#### 2. The ERANOS deterministic model

The code version used is ERANOS 2.0 [8]. The energy grid is constituted by 38 groups. The model [9] is based on axial-symmetric cylindrical geometry in order to describe accurately the shape of the core and of the reflector (Fig. 8). Owing to this choice, the polar asymmetries, such as the radial channel 1, the diametral channel or the different displacement of the control rods, cannot be described.



Fig. 8. TAPIRO geometry implemented in ERANOS.

For the generation of cross sections in the module ECCO, the radial domain is divided into different sections (those indicated in Fig. 7) to preserve the spectrum at the height of the centre of the core z<sub>core</sub>, in correspondence to the radial channel 1. The spectrum in the core is calculated with the standard cell calculation approach adopted for fissile media, while the surrounding regions are source-injected with a spectrum characteristic of the inner-adjacent region. Materials placed in different sections are considered in different cells. All the materials are treated in the cell definition as homogeneous infinite media. The Np-237, U-235 and U-238 cross sections are computed as for the other non fissile materials in the reactor, even if they are not considered in the geometry construction: the fission chambers are so small that no self-shielding is present. As a consequence, it is useless to model exactly the fission chamber in the geometry, since practically no spatial phenomenon is present. Moreover, the fission chambers cannot be modelled in the exact position of the measurements in the radial channel 1, owing to the cylindrical model adopted.

The spectral indexes (Eq. (1)) are presented in Fig. 9 in the different regions considered in the ECCO module for the source definition: the spectrum softens gradually moving away from the core (due to the interaction with matter and the greater leakage of fast neutrons with respect to thermal neutrons), as the value of the flux in the thermal and epithermal energy groups becomes of the same order of the source and overcomes it in the region Cu2, SH1 and SH2.



Fig. 9. Spectral indexes in different regions computed in ERANOS.

An analysis of the structure of the energy discretisation is performed, considering the value of the fission rates for the different isotopes. The energy grids are constructed adding to the reference 33-group energy discretisation, usually employed for fast reactor analysis, a finer discretisation of the lower groups. This is done because the thermal contribution may be relevant for the simulation of the experimental measurements. The 38-group structure is adopted once it is verified that the reaction rates cease to vary by adding further groups.

The dimension of the biological shielding, in particular in the radial direction, is very large with respect to the furthest point of measurements for all the nuclides, therefore it is not necessary to model the real shielding dimension. To select the shielding dimension in the model, an analysis of the dependence of the fission rates of each isotope on the shielding dimension is carried out, identifying an optimal radial and axial thickness of the shielding as 30 cm.

The discretisation of the solid angle is performed applying an  $S_{16}$  approximation. The tolerance on the flux is set to  $10^{-4}$ , instead the convergence on the effective multiplication eigenvalue  $k_{eff}$  is reached setting a tolerance of  $10^{-6}$ . The  $P_0$ order approximation is chosen for describing the anisotropy of the scattering. On the upper, lower and outer limits of the biological shielding, the void boundary condition is imposed. Consistent with the SERPENT model, the cross sections are calculated at 293 K. The libraries used are those from JEC-COLIB2 [8] (whose data are derived from JEF-2.2 [10]) and are structured according to the ECCO 1968-group, XMAS 172-group and ECCO 33-group configurations. Not all nuclides, in particular copper, are present in the library with finest energy discretisation, which has consequences on the accuracy of the condensation process.

## **IV. RESULTS**

In this section, computational results are presented and are compared to the measurements obtained from the experiments. The results shown include those of the SERPENT Monte Carlo model, those of the ERANOS deterministic model and, finally, those of a preliminary sensitivity study on the nuclear data libraries and on the effect of the properties of copper.

#### 1. The SERPENT results

The experimental fission rates traverses of Np-237, U-238 and U-235, measured along the radial channel 1, are compared with the ones computed by the model previously explained adopting some "virtual" detectors: the reactions (whose type has to be selected for a "virtual" material assumed to be the active part of the detector) are scored in a defined volume. This approach does not influence the random walk of the neutrons, since streaming and collisions are determined on the basis of the background material. Therefore, it is possible to compute a fission rate traverse in multiple positions in one simulation, since the virtual detectors do not affect each other. To not model the presence of the fission chamber is not expected to affect the results, since the true dimension of the fission chamber is quite small. The virtual detectors are placed in the exact position of the points of measurement of each isotope.

The dimension of the virtual detectors (Table III) is much larger than that of the miniature fission chambers in order to obtain acceptable statistics in reasonable computational time. Nevertheless, the geometrical form of the detector is such that the total volume remains contained within the access groove, maximizing the cross section and maintaining the dimension along the axis of the radial channel small relative to the distances over which the greatest variation of the reaction rate occurs. In addition, the access groove has a very small cross section: for the reasons of statistics and computational time, the modelled access groove is larger than the real one. To explore this approximation effect, two access groove models are investigated, varying its dimension. As a consequence, the detector cross section is limited by the access groove dimension, while the dimension along the axis of radial channel 1 (the x-axis) is unchanged. As the approximation of the access groove dimension is rather strong, the effect of modelling the access groove as a cylindrical channel (Fig. 5 a)) is expected to be negligible with respect to the dimension approximation.

TABLE III. Characteristics of the virtual detectors and the modelled access groove.

Access groove model	Small	Large
Detector volume [cm <sup>3</sup> ]	0.10	0.24
x-dimension [cm]	0.12	0.12
y-dimension [cm]	0.91	1.41
z-dimension [cm]	0.91	1.41
Access groove radius [cm]	0.66	1.065

The fission rate distributions of some isotopes are shown to evidence the difference of the results obtained by the two access groove models and comparing them to the experiments.

The comparison is made between simulations that adopt the same simulation parameters. In this situation, the relative standard deviation obtained with the large access groove model is lower than with the small access groove model, as the former permits a larger detector volume and therefore a better statistics. Data are presented as normalised to the integral along the traverse. The normalisation is necessary, since experimental values are given as count rates, depending on the efficiency of the detection system. Moreover, the normalisation overcomes the problem of selecting the exact power of the reactor maintained during the experiment and of knowing the exact amount of fissile material in the fission chambers. The uncertainties of all quantities presented, both experimental and computed (regardless of the model of the access groove), are very small.

From the comparison presented in the Fig. 10 it can been seen that the fission rate distribution of the U-235 in the first part of the traverse does not change so much between the two access groove models. This behaviour is verified also in the second part of the traverse. The agreement of the simulations with the measurements is quite good.



Fig. 10. Comparison of the normalised experimental and computed fission rates of U-235 in the first part of the traverse (Fig.4 b)): a) Large Access Groove model (L.A.G.); b) Small Access Groove model (S.A.G.). The zoom shows the error bar (otherwise too small). The radius is along the x-axis.

In the second part of the traverse, the Np-237 fission rates (Fig. 11) computed using the small access groove model decrease faster than those obtained by the large access groove model, departing from the experimental curve. The results of the latter model show good agreement with the measurements in the copper reflector region. It is seen that the experiment shows a different behaviour at great radial distances from the core, where the configuration of the experiment may change, leading to a discrepancy between the results and the experiment in this region. However, outside of the reflector, the results are less relevant for the characterisation of the reactor.



Fig. 11. Comparison of the normalised experimental and computed fission rates of Np-237 in the second part of the traverse (Fig.4 c)): a) Large Access Groove model (L.A.G.); b) Small Access Groove model (S.A.G.). The zoom shows the error bar (otherwise too small). The radius is along the x-axis.

Regarding the results of the small access groove model, decreasing the dimension of the access groove implies increasing the quantity of absorbing material around the detector: copper in the reflector region (x<41 cm) and concrete in the shielding region (x>41 cm). As a consequence, more neutrons are absorbed in the energy range in which the Np-237 fission cross section is quite high and the fission rate decreases rapidly along the radial channel 1. The Np-237 fission rate distribution in the first part of the traverse computed by the small access

groove model has a better agreement with the experiments than the results obtained by the large access groove model: since the dimension of the access groove in the former model is closer to the reality, the role of the captures in copper is better described. Instead, the inability to represent the change in behaviour of the fission rate distribution in the second part of the traverse renders more difficult to evaluate the adequacy of the two access groove models on the basis of this comparison.

The U-238 fission rate in the second part of the traverse (Fig. 12), like in the first part, is a good example in which there is a net improvement through the use of the small access groove model in comparison to the large access groove model. As for Np-237, in the former model there is a relatively larger quantity of absorbing material than in the large access groove model, which leads to a faster decrease of the fission rate along the axis of the channel and a better agreement with the experimental curve.



Fig. 12. Comparison of the normalised experimental and computed fission rates of U-238 in the second part of the traverse (Fig.4 c)): a) Large Access Groove model (L.A.G.); b) Small Access Groove model (S.A.G.). The zoom shows the error bar (otherwise too small). The radius is along the x-axis.

In general, it is possible to state that the access groove approximation has a greater impact on the fission rates of the isotopes Np-237 and U-238, hence the small access groove model is the preferred choice to correctly describe their fission rates. Instead, it may be appropriate to utilise the large access groove model to compute the U-235 fission rates, as the large and small access groove models yield similar results; this allows to save computational time.

In Fig. 13, the relative standard deviations of the computed reaction rates obtained by the small access groove model (which is characterised by the worst statistics) are illustrated, comparing them with the relative error on the experimental measurements. It is possible to observe that the magnitudes of the experimental and computed relative standard deviations are comparable, indicating that the input parameters that regulate the statistics are appropriate.



Fig. 13. Comparison between the relative standard deviation of the computed (a) and c) ) and measured fission rates (b) and d) ) in the two parts in which the radial channel 1 has been divided in the simulations: a) and b) refer to the first part of the traverse, c) and d) to the second part.

### 2. The ERANOS results

In this section, the fission rates distribution in the radial channel 1 obtained by the deterministic model are compared with the experiments and the Monte Carlo results. The comparison is among these integral responses normalised to their integral along the traverse, for the same reasons reported in the previous section.

The choice of the spatial grid in the deterministic simulation does not correspond to the measurement points, since it must guarantee a good quality of the results. The normalisation is carried out by a fitting procedure: this is particularly needed for the experimental and SERPENT results.

The fission rate distribution  $R_f$  for nuclide *i* along the traverse is calculated as follows:

$$R_{f,i}(r_j, z_{core}) = \sum_{g=1}^{NG} \Sigma_{f,i,g}(r_j) \Phi_g(r_j, z_{core}).$$
(3)

The fission cross section  $\Sigma_f$  is spatially dependent along the traverse owing to the fact that the neutron spectrum used for the its evaluation may change.

In Fig. 14, the agreement between the experimental and computed fission rates by the ERANOS model of the Np-237 is good in the first part of the traverse. Approaching the boundary between the shielding and the outer reflector the discrepancy between the two results increases: the slope of the computed results changes near the OR-SH interface, while for the experimental ones the change of slope occurs at a greater distance. Moreover the deterministic curve decreases faster than the experimental one. A possible cause of the discrepancy could be the limited energy refinement of the library used by ECCO for the condensation process. A good refinement is necessary for Np-237 in the epithermal energy range, owing to the large number of resonances of the fission cross section, which is shown in Fig. 15: the difference in the resonance region is apparent between the continuous energy and the discrete energy libraries. A similar explanation can be applied for the comparison on the U-238 fission rate distribution (Fig. 16), since the energy dependence of the U-238 and Np-237 fission cross sections is similar.



Fig. 14. Comparison among the normalised Np-237 fission rates measured and computed by SERPENT and by ERANOS.



Fig. 15. Fission cross section of Np-237, comparing the continuous energy cross section of the JEF-2.2 library [10] and the condensed cross section of the JECCOLIB2 library [8].



Fig. 16. Comparison among the normalised U-238 fission rates measured and computed by SERPENT and by ERANOS.

The U-235 fission rate ERANOS-computed curve (Fig.17) decreases faster in the copper reflector region than the experiments. This dissimilarity does not arise in SER-PENT simulations. Therefore, it is reasonable to investigate on the different libraries used in SERPENT and ERANOS simulations and, in particular, on the cross section of copper.



Fig. 17. Comparison among the normalised U-235 fission rates measured and computed by SERPENT and by ERANOS.

As it is possible to see from Fig. 18, the treatment of the resonances of the capture cross section in JEF-2.2 is quite inaccurate with respect to JEFF-3.1.1. The overestimation of the resonance values of the capture cross section could lead to more capture of the epithermal neutrons, and then to a lower number of neutrons that slow down to the thermal energy, where the fission cross sections of U-235 is quite high. Moreover, the most refined energy library provided as starting library for the energy condensation of natural copper is the XMAS 172-group structure. This leads to a poor treatment of the resonance region of the copper cross section in the ERANOS model, which is already limited by the inaccuracies of the JEF-2.2 library in comparison to the JEFF-3.1.1 library.



Fig. 18. Capture cross section of copper in JEFF-3.1.1 pointwise library [7] (used in SERPENT simulation), in JEF-2.2 pointwise library [10] (used by JECCOLIB2 library) and in JECCOLIB2 library [8] (used in ECCO). Also shown are the spectral indexes of the flux in the Cu1 and Cu2 zones computed with ERANOS.

#### 3. The preliminary sensitivity analysis

The effect of adopting different libraries is explored by the use of the SERPENT model of TAPIRO, in conjunction with two different nuclear data libraries, JEF-2.2 and JEFF-3.1.1. A negligible effect on the neutron spectrum is seen in Fig. 19; this is also true when considering the reaction rates. On the other hand, the value of  $k_{eff}$  changes significantly, as shown in Table IV: the data reported are extracted from the simulations performed using the two libraries in the configuration illustrated in Fig. 4 c).



Fig. 19. Comparison of the spectral indexes in the different regions obtained from the use of two different libraries in SERPENT: JEFF-3.1.1 and JEF-2.2. The set-up of the two simulations is that illustrated in Fig. 4 c).

In order to explore the effect of the variation of the copper cross section on the integral responses analysed, a preliminary sensitivity analysis is performed in ERANOS, varying the

TABLE IV. The  $k_{eff}$  values obtained by the SERPENT simulations with two different libraries: JEFF-3.1.1 and JEF-2.2.

	JEFF-3.1.1	JEF-2.2
$k_{eff}$ Relative $\sigma$ on $k_{eff}$	1.00787 4 9E-06	1.00874 4 9E-06
Relative variation [pcm]	-	-86.3207

atomic density in the neighbourhood of its reference value. The response on the fission rate distributions is observed at selected positions, chosen to show the variation of the response behaviour to the modification.

The relative variation of the U-238 fission rate as a function of the relative variation of the atomic density of copper (Fig. 20) shows a monotonic decreasing trend. Moving away from the core the response is no longer linear, but shows a positive concavity that increases at larger radii (where the fission rates of the two nuclides are smaller): the effect is larger in the negative range of variation of the copper atomic density. The behaviour for Np-237 is similar to U-238.



Fig. 20. Relative variation of the U-238 fission rate as a function of the relative variation of the atomic density of copper with respect to the reference value at different radii along the radial channel 1.

At the beginning of the traverse, where the neutrons have a higher energy, the U-235 fission rate increases if the atomic density of copper increases (Fig. 21). In the hard spectrum region the scattering-capture ratio for copper is higher than in the lower part of the spectrum, leading in an increase in the U-235 fission rate. Indeed, in this first part of the traverse, the sensitivity of the fission rates to the variation of the atomic density of copper is not very relevant. Gradually the trend reverses and, at radii larger than about 17 cm, the curves begin to decrease: as the spectrum is more thermalised, the copper captures become more important, which leads to a decrease of the U-235 fission rate.

In general, the response of the fission rates of the isotopes considered to the copper cross section variation is linear just at the beginning of the radial channel 1, where the spectrum is fast. Consequently, an analysis based on perturbation theory would have a very limited range of validity.



Fig. 21. Relative variation of the U-235 fission rate as a function of the relative variation of the atomic density of copper with respect to the reference value at different radii along the radial channel 1.

## **V. CONCLUSIONS**

The Monte Carlo SERPENT code and the deterministic code ERANOS are adopted for the simulation of the TAPIRO reactor and the reconstruction of some measured quantities. The reaction rates measured in one experimental channel are compared to simulation results. The analysis allows to evidence the effects connected to the adoption of different modelling approaches and different nuclear data libraries.

The discrepancies in the results indicate that nuclear data should be improved. In particular, the copper properties have a relevant effect on the neutronics of this system. The improvement of the knowledge of the properties of copper is of relevance also in other fields where this element plays an important role, such as applications in fusion technology. The same applies for actinides data, the relevance of which is highly important in advanced nuclear systems.

In the prosecution of the work, a thorough sensitivity analysis will be performed and a proposal for new measurements for the improvement of cross section data are foreseen.

### VI. ACKNOWLEDGEMENT

This work is carried out in the framework and with the financial support of 'Accordo di Programma Ministero dello Sviluppo Economico - ENEA sulla Ricerca di Sistema Elettrico' and of CIRTEN (Consorzio Interuniversitario per la Ricerca Tecnologica Nucleare).

## REFERENCES

- ENEA, "TAPIRO," http://www.enea.it/en/researchdevelopment/documents/nuclear-fission/tapiro-eng-pdf, accessed: 18 July 2016.
- Y. RONEN, Uncertainty analysis, CRC Press, Boca Raton (2000).
- 3. C. BETHAZ, Feasibility analysis on irradiation of actinides in TAPIRO fast reactor with Monte Carlo methods,

Master's thesis, Politecnico di Torino, Italy (2015).

- A. FABRY, P. MOIOLI, M. ANGELONE, M. CARTA, G. ROSI, A. DI MODUGNO, R. SCAFE, D. ANTONINI, E. D. MCGARRY, P. D'HONDT, F. COPS, G. MINSART, J. LACROIX, H. AÏT ABDERRAHIM, G. DELEEUW, and D. LANGELA, "Neutronic characterization of the TAPIRO fast-neutron source reactor," Final report, SCK-CEN, Mol (1986).
- 5. J. LEPPÄNEN, *Development of a new Monte Carlo reactor physics code*, Ph.D. thesis, VTT Technical Research Centre of Finland, Finland (2007).
- 6. O. DICUONZO, Simulations of experimental measurements in the TAPIRO reactor by Monte Carlo and deterministic methods, Master's thesis, Politecnico di Torino, Italy (2016).
- A. SANTAMARINA, D. BERNARD, P. BLAISE, M. COSTE, A. COURCELLE, T. HUYNH, C. JOUANNE, P. LECONTE, O. LITAIZE, S. MEN-GELLE, G. NOGUÈRE, J.-M. RUGGIÉRI, O. SÉROT, J. TOMMASI, C. VAGLIO, and J.-F. VIDAL, "The JEFF-3.1.1 nuclear data library (JEFF report 22)," Tech. Rep. NEA No. 6807, Nuclear Energy Agency, Paris (2009).
- G. RIMPAULT, D. PLISSON, J. TOMMASI, R. JACQMIN, J.-M. RIEUNIER, D. VERRIER, and D. BIRON, "The ERANOS code and data system for fast reactor neutronic analyses," in "International Conference PHYSOR 2002," Seoul, Korea (2002).
- P. BLAISE, M. CARTA, S. DULLA, V. FABRIZIO, A. GANDINI, B. GESLOT, A. GROSSI, V. PELUSO, and P. RAVETTO, "Feasibility of experiments in the TAPIRO reactor to improve minor actinides nuclear data," in "14th Information Exchange Meeting on Actinide and Fission Product Partitioning and Transmutation," San Diego, CA (2016).
- OECD/NEA, "The JEF-2.2 nuclear data library (JEFF report 17)," Tech. rep., Nuclear Energy Agency, Paris (2000).