

Analysis of High Pressure In-Vessel Late Phase Melt Progression in the Korean Standard Nuclear Power Plant

150

SCDAP/RELAP5/MOD3.3

가
가 , 30 % 가
가
4 가
50-60 % 가

Abstract

High-pressure in-vessel melt progressions of the KSNP (Korean Standard Nuclear Power Plant) have been analyzed using the SCDAP/RELAP5/MOD3.3 computer code. The total loss of feed waters (LOFW) to steam generators with/without intentional RCS depressurization using the safety depressurization system and the station blackout (SBO) have been simulated from transient initiation to reactor vessel failure. The SCDAP/RELAP5/MOD3.3 results have shown that the pressure boundary of the reactor coolant system did not fail before reactor vessel failure in the high-pressure sequences of the LOFW and the SBO transients. In all high-pressure transients, approximately 30 % of the core material was melted and relocated to the lower plenum of the reactor vessel at the time of reactor vessel failure. The LOFW with intentional RCS depressurization using the safety depressurization system delays reactor vessel failure time for approximately 4 hours and more by actuation of the safety injection tanks. At the time of reactor vessel failure, approximately 50-60 % of the fuel rod cladding was oxidized in the LOFW and the SBO transients of the KSNP.

1.

(late phase melt progression)

(ballooning)

(steam starvation),

eutectic

pool

PBF[1], FLHT[2], Phebus[3],

CORA[4], OECD-LOFT[5]

가

SONATA

[6]

OECD/NEA

MASCA

[7]

[8]

가

가

가

가

가

가 (Direct Containment Heating)

(early containment failure)

가

[8].

2

가

(Safety

Depressurization System: SDS)

가

seal

가

가

가

가

가

가

SCDAP/RELAP5/MOD3.3[10]

2

(Total Loss of Feed Water: TLFW)

(Station Blackout: SBO)

2.

2 가
 , 가

2
 가 .

INEEL USNRC 2001
 SCDAP/RELAP5/MOD3.3 . SCDAP/RELAP5
 RELAP5/MOD3 [11],
 SCDAP/MOD1 [12], (Finite
 Element Method) COUPLE [13] 가
 가 .

SCDAP/RELAP5 1988 version MOD0가
 가 . 2001 SCDAP/RELAP5/MOD3
 FCI(Fuel Coolant Interaction) 가,
 , pool

SCDAP/RELAP5/MOD3.3
 . 1
 , 가 , ,
 . 3
 channel channel cross flow junction 가
 . 3 component 3 component 6
 10 node . component
 6 , 2 node .
 COUPLE .
 가 2
 가
 , , 가
 . 2 .
 vessel, , 가 surge ,

creep

가

가

3.

1

SCDAP/RELAP5/MOD3.3

가

가

가

가

가

가

가

40

가

가

10

가

4

2

가

SCDAP/ RELAP5/MOD3.3

가

가

가

가

10

가

가

가

가

가

3

가

SCDAP/RELAP5/MOD3.3

가

가

가

가

가

가 가

가

가

가

가

가

가

가

가

가

4

SCDAP/RELAP5/MOD3.3

가

가

가 가 가 . 가
가 가 가 . 가
가 가 가 . 가
5 SCDAP/RELAP5/MOD3.3 . 가
가 가 가 . 가
6 MOD3.3 SCDAP/RELAP5/
가 , 가 1,700 K 가 1,000 K . 1
가 가 가 가
7 8 SCDAP/RELAP5/MOD3.3 .
가
9 SCDAP/RELAP5/MOD3.3 .
30 % 2
0.8 m
10 11 SCDAP/RELAP5/MOD3.3
2
2,850 K .

4.
SCDAP/RELAP5/MOD3.3

가

가

, 30 %

가

가

가

가 40

4

가

가

가

50-60 %가

1. D. A. Petti et al., "PBF Severe Fuel Damage Test 1-4 Test Results Report," NUREG/CR-5163, EGG-2542, December 1986
2. D O. Lanning and N. J. Lombardo, "Data Report for Full Length High Temperature Experiments," PNL-6540, April 1988
3. G. Repetto et al., "The First PHEBUS Fission Product Experiment FPT0 General Aspects of the Experimental Sequence Concerning the Fuel Bundle Degradation and FP Release," ANS Int. Topical Meeting on the Safety of Operating Reactors, Seattle, Sep. 17-20, 1995
4. S. Hargen et al. "Results of SFD Experiment CORA-13 (OECD International Standard Problem 31)," KfK 5054, Kernforschungszentrum Karlsruhe, February 1993
5. D. Osetek, "Overview of the OECD LOFT FL-2 Test," Presented at the SFD/ST Research Program Review Meeting, Idaho Falls, Idaho, April 10-14, 1989
6. S. B. Kim, K. Y., Suh, "Progress in SONATA-IV," OECD/NEA CSNI Special Meeting on In-Vessel Debris Coolability and Lower Head Integrity, Paris, France, 1996
7. OECD/NEA, "Agreement on the OECD MASCA Project," 2000
8. Kim Y. H., Suh K. Y., "Sensitivity Analyses for Maximun Heat Removal from Debris in the Lower Head," J. of the Korean Nuclear Society 32 (4), 395-409, 2000
9. , " 1 , 1 , " , '90 , 1990 5 25
10. L. J. Siefken et al., "SCDAP/RELAP5/MOD3.3 Code manual," NUREG/CR-6150, INEL-96/0422, January 2001
11. The RELAP5 Development Team, "RELAP5/MOD3 Code Manual," NUREG/CR-5535, INEL95/0174, August 1995
12. C. M. Allison et al. "SCDAP/MOD1/V0: A Computer Code for the Analysis of LWR Vessel Behavior During Severe Accident Transients," IS-SAAM-83-002, July 1984
13. E. C. Lemmon, "COUPLE/FLUID: A Two Dimensional Finite Element Thermal Conduction and Advection Code," EGG-ISD-SCD-80-1, February 1980

1.

SCDAP/RELAP5


/MOD3.3 (:)

	0	0	0
	-	1,905	-
	2,985	2,769	5,637
	-	3,590	-
	4,749	4,050	7,178
	5,829	22,796	8,483
	5,910	23,235	8,570
(%)	56.9	47.3	57.5

2.


SCDAP/RELAP5/MOD3.3

()	5,910	23,235	8,570
	38.6	27.5	35.1
(m)	0.82	0.88	0.72
(m ³)	3.88	4.42	3.05
(ton) (=109.5)	29.8	34.4	23.5
(ton) (=85.6)	23.6	27.4	18.6
ZrO ₂ (ton)	4.3	4.0	3.2
Zr (ton) (=23.9)	1.9	3.0	1.7
(K)	2,843	2,856	2,840
(MW/ m ³)	2.74	1.99	2.50




1.


SCDAP/RELAP5 Nodalization



2. 가 SCDAP/RELAP5




3. 가 SCDAP/RELAP5




4.

SCDAP/RELAP5




5.

SCDAP/RELAP5




6.

SCDAP/RELAP5




7.

SCDAP/RELAP5




8.

SCDAP/RELAP5




9.

SCDAP/RELAP5



10.

SCDAP/RELAP5



11.

SCDAP/RELAP5